

BF2.3 PORTABLES



- 1 World's lightest four-stroke
- 1 World record fuel economy
- 1 15 & 20 inch available
- 1 Air cooled
- 1 Only 13.4 kg (30 lb.)



ENGINE

| | | | |
|--|--|--------------------------------|-------------------------------------|
| Type | 4-Stroke, OHV; 1 Cylinder / 2 Valves | Displacement | 57 cc / 3.5 cubic in. |
| Bore & Stroke | 45 mm x 36 mm (1.77 x 1.42 in.) | Full Throttle RPM Range | 5,000-6,000 RPM |
| Propshaft Rated Horsepower (HP) | 2.3 hp @ 5,500 RPM | Cooling System | Air Cooled |
| Fuel Delivery | 1 Carburetor | Recommended Fuel | Unleaded Gas. (Min. Pump Octane 86) |
| Ignition System | Transistorized Magneto Ignition | Starting System | Recoil |
| Exhaust | Under Water, above propeller | Lubrication | Forced splash |
| Recommended Oil | SAE 10W30 API service classification SJ or later | Oil Capacity | 0.25 L (0.22 Imp. qt) |
| Trim Range | 4-Stage 5°-10°-15°-20° | Tilt Range | 75° |
| Steering Angle | N/A | | |

DRIVE

| | | | |
|-------------------|--------|-------------------|------------------------------|
| Gear Ratio | 2.42:1 | Gear Shift | F & N - 360° Swivel Steering |
|-------------------|--------|-------------------|------------------------------|

EQUIPMENT

| | | | |
|------------------------------------|----------|------------------------------------|----------|
| Alternator (Manual Start) | N/A | Alternator (Electric Start) | N/A |
| Battery Charging Power | N/A | Power Tilt | N/A |
| Power Trim & Tilt | N/A | Gas Assisted Tilt | N/A |
| Oil Pressure Alert | Standard | Over Rev-Limiter | Standard |
| Temperature Alert | N/A | Water in Fuel Alert | N/A |
| Battery Condition Alert | N/A | Speedometer Pickup | N/A |
| Variable Speed Trolling Kit | N/A | Rudder Meter Kit | N/A |
| Tilt limit Kit | N/A | | |

DIMENSIONS

| | | | |
|-----------------------------------|-------------------|--------------------------------|-------------------|
| Overall Width | 285 mm / 11.2 in. | Transom Height (S-Type) | 418 mm / 16.5 in. |
| Transom Height (SCHC-Type) | N/A | Transom Height (L-Type) | 572 mm / 22.5 in. |
| Transom Height (LCHC-Type) | N/A | Transom Height (X-Type) | N/A |
| Transom Height (XX-Type) | N/A | | |

PROPELLER

| | | | |
|--|-------------------------------------|--|-------------------------------------|
| Propeller Type | 3-Blade (Polymer) | Propeller Diameter x Pitch (S-Type) | 184 mm x 120 mm / 7-1/4 x 4-3/4 in. |
| Propeller Diameter x Pitch (L-Type) | 184 mm x 120 mm / 7-1/4 x 4-3/4 in. | Propeller Diameter x Pitch (BF(P) Models) | N/A |

DRY WEIGHT

| | | | |
|------------------|-----|------------------|--|
| S type | N/A | SCHC-Type | 13.6 kg / 30 lbs. (With propeller mounted) |
| SHGC-Type | N/A | SHS-Type | N/A |

| | | | |
|------------------|--|------------------|-----|
| SRC-Type | N/A | L type | N/A |
| LCHC-Type | 14.3 kg / 31.5 lbs. (With propeller mounted) | LHGC-Type | N/A |
| LRTC-Type | N/A | X-Type | N/A |
| XC-Type | N/A | XRTC Type | N/A |
| XX Type | N/A | | |

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.