

# BF50 MID-RANGE



- 1 BLAST<sup>®</sup> (Boosted Low Speed Torque) technology
- 1 Lean Burn Control<sup>®</sup>
- 1 Multi-port Programmed Fuel Injection
- 1 Lightest weight in class
- 1 Best-in-class fuel efficiency



## ENGINE

<b>Type</b>	4-Stroke SOHC; 3 Cylinders / 6 Valves	<b>Displacement</b>	808 cc / 49.4 cubic in.
<b>Bore &amp; Stroke</b>	70 mm x 70 mm (2.76 x 2.76 in.)	<b>Full Throttle RPM Range</b>	5,500-6,000 RPM
<b>Propshaft Rated Horsepower (HP)</b>	50 hp @ 5,750 RPM	<b>Cooling System</b>	Water Cooled
<b>Fuel Delivery</b>	Programmed Electronic Fuel Injection (PGM-FI)	<b>Recommended Fuel</b>	Unleaded Gas. (Min. Pump Octane 86)
<b>Ignition System</b>	MicroComputer Programmed	<b>Starting System</b>	Electric
<b>Exhaust</b>	Through Prop Hub	<b>Lubrication</b>	Pressure Lubrication (Trochoid pump)
<b>Recommended Oil</b>	SAE 5W30 API service classification SJ or later	<b>Oil Capacity</b>	2.10 L (1.85 Imp. qt) with oil filter repl.
<b>Trim Range</b>	-4° to +12°	<b>Tilt Range</b>	63°
<b>Steering Angle</b>	35°		

## DRIVE

<b>Gear Ratio</b>	2.08:1	<b>Gear Shift</b>	F-N-R
-------------------	--------	-------------------	-------

## EQUIPMENT

<b>Alternator (Manual Start)</b>	N/A	<b>Alternator (Electric Start)</b>	22 amp / 275 watts
<b>Battery Charging Power</b>	17 amp	<b>Power Tilt</b>	N/A
<b>Power Trim &amp; Tilt</b>	LHTC & LRTC models	<b>Gas Assisted Tilt</b>	N/A
<b>Oil Pressure Alert</b>	Standard	<b>Over Rev-Limiter</b>	Standard
<b>Temperature Alert</b>	Standard	<b>Water in Fuel Alert</b>	N/A
<b>Battery Condition Alert</b>	Standard	<b>Speedometer Pickup</b>	Standard
<b>Variable Speed Trolling Kit</b>	Optional	<b>Rudder Meter Kit</b>	N/A
<b>Tilt limit Kit</b>	N/A		

## DIMENSIONS

<b>Overall Width</b>	372 mm / 14.6 in.	<b>Transom Height (S-Type)</b>	N/A
<b>Transom Height (SCHC-Type)</b>	N/A	<b>Transom Height (L-Type)</b>	556 mm / 21.9 in.
<b>Transom Height (LCHC-Type)</b>	N/A	<b>Transom Height (X-Type)</b>	N/A
<b>Transom Height (XX-Type)</b>	N/A		

## PROPELLER

<b>Propeller Type</b>	3-blade (Aluminum)	<b>Propeller Diameter x Pitch (S-Type)</b>	N/A
<b>Propeller Diameter x Pitch (L-Type)</b>	11-1/4 x 13 in.	<b>Propeller Diameter x Pitch (BF(P) Models)</b>	N/A

## DRY WEIGHT

<b>S-Type</b>	N/A	<b>SCHC-Type</b>	N/A
<b>SHGC-Type</b>	N/A	<b>SHS-Type</b>	N/A

<b>SRC-Type</b>	N/A	<b>L-Type</b>	N/A
<b>LCHC-Type</b>	N/A	<b>LHGC-Type</b>	N/A
<b>LRTC-Type</b>	98 kg / 216.1 lbs.	<b>X-Type</b>	N/A
<b>XC-Type</b>	N/A	<b>XRTC Type</b>	N/A
<b>XX Type</b>	N/A		

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.